

Gruetzner LUB-S

Monitored lubrication
of minimum volume



Advantages



Flexible use

up to 3 operating modes
battery operation or with 24 VDC



Detailed monitoring

optical function and fault
indication by LEDs



Connection to PLC possible

pulse-controlled lubricant delivery



High operating pressure

up to 50 bar (745 psi)



Further advantages

- suitable for splitters / progressive distributors
- compact dimensions

Technical data

Piston

Lubricant cartridge

Battery (LUB-S-B)

Display

Drive

Housing

Outlet M16x1.5 / M10x1



Drive

electromechanical

Operating pressure

max. 50 bar (725 psi)

Distribution period

1-24 months
time mode or pulse control

Lubricant volume

125 ml / 250 ml

Operating temperature

-15 °C to +60 °C

Working voltage

6,0 V (battery) or 24 VDC

Lubricating medium

oils and greases up to NLGI 2

Filling

standard filling/special filling

Dimensions (height x Ø)

152 x 83 mm

Performance monitoring

display & LED

Areas of application



LUB-S can be used as single point lubricator or as multipoint lubricator. Due to its extremely compact pump unit and its low weight it especially suits applications with lacking space.



GRUETZNER
AUTOMATIC LUBRICATION

Gruetzner GmbH
Dagobertstr. 15 • 90431 Nuremberg, Germany
tel. +49 911 277 399 0
info@G-LUBE.com • www.G-LUBE.com